

## DECLARATION OF CONFORMITY

Nr. CE/PLA/02-14s

03-06-2015

### Manufacturer and address:

„Plankmara“ JSC, Taikos str. 78, Uzusaliai village, Jonava district, LT-55333, Lithuania

### Product description:

Solid wood floorboards with tongue and grooves, made of European-oak (*Quercus petraea*). Standard dimensions of floorboards: 14x90x500-1100 mm, 14x130/150/180x500-2450 mm, random lengths. Designed for indoor use, gluing the boards to the ground with or without an air gap, in accordance with the manufacturer's requirements ([www.staki.lt](http://www.staki.lt)). All cracks and knots are filled and sanded, the plank surface can be additionally structured-brushed, with mechanical tappings - aged. The surface is finished with hardwax oil „Saicos Premium Hardwax“ from producer SAICOS COLOUR GmbH, Germany.

### Declared performance:

The main characteristics	Performance declaration	Certificate / Report number
1. Reaction to fire:	C <sub>fl</sub> -s1	EN 14342:2013
2. Emission of formaldehyde:	E1	R.N. 630
3. Content of PCP:	≤ 5 ppm	EN 14342:2013
4. Breaking strength:	NPD	EN 14342:2013
5. Slipperiness:	43	R.N. 637
6. Thermal conductivity:	0,18 W/mK	R.N. 046/15-3
7. Biological durability:	1 class	EN 14342:2013

### Conformity declaration basis:

„Plankmara“ JSC declares that „Plankmara“ JSC produced solid oak floorboards are manufactured and labeled in the Construction Products Directive (Council Directive 89/106/EEC) and the Harmonized European standard EN 14342:2013 (Wooden floors and parquet. Characteristics evaluation of conformity and labeling) requirements in Annex ZA system 4, based on KTU Architecture and construction Institute of physics laboratory testing protocol No. 046/15-3 and „Alzida“ JSC, accredited building materials and product testing laboratory, testing protocols R.N. 630, R.N. 637.

### Special conditions of use of the product:

The manufacturer guarantees product quality on the delivery time, when the floor is installed and operated in accordance with EN 14342:2013 requirements and the manufacturer's recommendations. Detailed information can be found on the packaging of the product and in the manufacturer's website [www.staki.lt](http://www.staki.lt).



„Plankmara“ JSC  
Taikos str. 78, Užusaliai village, Jonava district.  
LT-55333 Lithuania  
15

**EN 14342:2013**

Solid wood floorboards with tongue and grooves made of European-oak (*Quercus petraea*). Finished with hardwax oil „Saicos Premium Hardwax“.

Floorboards have to be glued to the ground with or without an air gap, indoor use.

Reaction to fire:	C <sub>fl</sub> – s1
- The lowest average density:	650 kg/m <sup>3</sup>
- The lowest total thickness:	14 mm
- The final conditions of use:	glued to the ground with or without an air gap
Emission of formaldehyde:	E1
Content of PCP:	≤ 5 ppm
Breaking strength:	NPD
Slipperiness USRV:	43
Thermal conductivity:	0,18 W/mK
Biological durability:	1 class

„Plankmara“ JSC  
S.P.



Gen. Director  
Kestutis Stakenas

sign